

IsatDock PRO



- Intelligent POTS/RJ11 Interface
- Speaker Phone
- Active Privacy Handset
- High Quality Docking Station

Beam IsatDock PRO is an intelligent docking station for the IsatPhone Pro specifically designed to support accessing voice services via Bluetooth, RJ11/POTS, handsfree speaker phone or the active privacy handset attached to the unit.

IsatDock PRO allows the IsatPhone Pro handset to be used in a wide variety of applications. The intelligent RJ11/POTS interface enables cable runs of up to 600m to connect standard corded, cordless or DECT handsets to be used or alternatively interfaced with a PBX system presenting standard ring, busy and dial tones like a standard phone network.

The IsatPhone Pro handset, fits securely in the dock which is also key lockable, other features include phone charging, USB data port, in-built ringer and allows antenna and power to be permanently connected to the dock ready for use. The IsatPhone Pro handset is easily inserted and removed by the press of a button on the top of the dock making it very easy to use away from the dock when required.











KEY FEATURES

DESIGN

- All in one design
- High quality ABS Plastic
- Single action insertion mechanism
- Key lockable & securable to wall/desk
- Wall or desk mounting options
- Accessible control buttons
- Slimline privacy handset
- Integrated antenna connections
- In-built speaker/microphone
- Cable routing LHS/TOP/BOTTOM

OTHER KEY FEATURES

- Active privacy handset
- In-built handsfree speaker phone
- Status LED with adjustable brightness
- USB data access

POWER

- 10-32V DC Input
- 110-240V AC plug pack, included

BUTTONS ON DOCK

- Ringer volume up/down
- In-call volume up/down
- Last number redial
- In-call mute
- Speaker/hands free button

INTELLIGENT POTS/RJ11 INTERFACE

- Support up to 600m of RJ11
- Dial, Ring & Busy Tones
- Integrates to PABX
- Support standard corded & cordless phones
- Auto-dial & speed dials available



Charging



Docking



POTS/RJ11



USB



Privacy Handset



Handsfree

RJ11/POTS INTERFACE

PSTN EMULATION

The RJ11/POTS interface emulates PSTN (Public Switched Telephone Network) features and is equipped with off-hook detection, configurable ring, busy & dial service tones.

The IsatDock PRO supports long runs of standard telephone wire and multiple extensions can be connected to the terminal over distances of up to 600m.

PBX INTEGRATION

Use of the intelligent RJ11 interface of the IsatDock PRO enables the easy integration with a PBX system within a building allowing for multiple user access to satellite calls where traditionally satellite reception is not accessible or convenient to use.

PRIVACY HANDSET

The IsatDock PRO comes with a Privacy Handset for voice calls. The handset is compact and provides private conversations in place of handsfree mode.

TECHNICAL SPECIFICATIONS

AVERAGE POWER CONSUMPTION CURRENT @ 12V	AVERAGE	WATTS	
Power w/o IsatPhone Pro	130mA	1.6W	
Standby + Charging	360mA	4.3W	
Transmit + Charging	875mA	10.5W	
Sleep Mode	5mA	60mW	
Peak Current	3.5A	42W	
PHYSICAL SPECIFICATIONS	5		
Dimensions	270 x 189 x 101 (mm)	10.6 x 7.4 x 4 (inches)	
Weight - Dock	1.45kg	3.19lbs	
Total Kit Weight	2.45kg	5.39lbs	
ENVIRONMENT SPECIFICATIONS			
Operating Range	-30°C to +70°C	-22°F to +158°F	
Storage	-35°C to +85°C	-31°F to +185°F	
Battery Charging Temp#	0°C to +45°C	32°F to +113°F	
Humidity		<= 75% RH	
CONNECTORS / INTERFAC	ES		
POTS/RJ11	RJ11/2-wire, 5REN @ 600m, Adjustable dial, ring, busy tone configured frequency and adaptive impedance.		
Inmarsat Antenna	TNC-Female		
GPS Antenna	SMA-Female		
10-32 V DC	4-way microFit (AC/DC adator, or DC lead)		
Privacy Handset Port	RJ9 connector		
Configuration/Data	USB Micro		
Speakerphone	In-built speaker/microphone		

# It is ideal for the ambient temperature to be approximately 18 degrees below the 45°C upp	
limit for the handset to charge the battery whilst docked.	

CERTIFICATIONS		
Inmarsat Type Approval		
FCC		
CE Compliance		
Electrical Safety		
RoHS		
Industry Canada		
C-Tick		
EMC compliance		
ACCESSORIES		
ISD700	IsatDock Fixed Passive Antenna	
ISD710	IsatDock Transport Active Antenna (Bolt)	
ISD715	IsatDock Transport Active Antenna (Magnetic)	
ISD932	IsatDock 6m SMA/TNC Active cable kit	
ISD933	IsatDock 13m SMA/TNC Active cable kit	
ISD934	IsatDock 18m SMA/TNC Active cable kit	
ISD935	IsatDock 31m SMA/TNC Active cable kit	
ISD936	IsatDock 10m SMA/TNC Passive cable kit	
ISD937	IsatDock 20m SMA/TNC Passive cable kit	
RST055	Beam UPS Battery Pack	
KIT CONTENTS		
IsatDock PRO		
110-240V AC Plug Pack		
Privacy Handset		
10-32V DC Power Cable		
Wall Mounting Plate		
Handset lock key		
User Manual & Quick Start Guide		



TOLL FREE 1-888-989-8199

1455 N. Dutton Suite A, Santa Rosa, CA 95401
FAX 707-546-8198 • info@remotesatellite.com
www.remotesatellite.com

www.beamcommunications.com



+61 3 8588 4500



+61 3 9560 9055



info@beamcommunications.com

AFRICA ASIA AUSTRALIA EUROPE MIDDLE EAST NORTH AMERICA SOUTH AMERICA