

Terra 800





Terra 800



Terra 800 is an all-in-one communications terminal, specifically designed to be utilized in a wide variety of land based applications; such as a dedicated telephone service or a back up emergency telephone system that can be deployed throughout the world.

Featuring an intelligent RJ11/POTS interface to enable connection of up to 5 standard corded/cordless phones or integration to a PABX system, supporting cable runs of up to 600m (2000') and presents standard ring, busy and dial tones.

The Terra 800 has an integrated Bluetooth for voice communications, intuitive color LCD display that provides easy and convenient access to send and receive SMS or to retrieve phone numbers stored in the terminal.

Other key features include, a secondary SIM socket to override internal SIM, an active privacy handset, in-built handsfree speakerphone, USB data, inbuilt phone book, SMS, adjustable ring tones, desk or wall mountable.

The Terra 800 is designed to operate with the Inmarsat "Link Phone" service and is supplied with a dedicated high quality directional/fixed antenna system to provide a completely integrated solution that is ready for use anytime.















Bluetooth

Muta





SIM

LCD Display





POTS/RJ11

USB





Privacy Handset

Handsfree



Remote Work Sites



Disaster Recovery



Remote School
Communications



Farm Houses

KEY FEATURES

DESIGN

- High quality IP54 rated enclosure
- Colour LCD Screen
- Compact all in one design
- · Wall or desk mounting options
- · Locking bolt to wall mounting
- Accessible control buttons
- · Integrated antenna connections
- · Slimline privacy handset
- In-built speakerphone
- Cable routing LHS/TOP/BOTTOM
- Dual SIM card enclosures

POWER

- 10-32V DC Input
- · 110/240V AC plug pack, included

INTELLIGENT POTS/RJ11 INTERFACE

- Support up to 600m (2000') of RJ11 cable runs
- · Standard dial, ring & busy tones
- Integrates easily to PABX System
- Support standard corded, cordless and DECT phones
- · Auto-dial & speed dials available

VOICE CALLING FEATURES

- Integrated easy to use phone book
- Privacy handset calling
- · In-built handsfree speakerphone
- · Access from PBX or other corded/cordless handsets
- · Bluetooth headsets (not included)

OTHER KEY FEATURES

- SMS
- Secondary and over riding accessible SIM port (credit card sized SIM)
- Phonebook
- Status LED
- Adjustable brightness
- USB data access

TECHNICAL SPECIFICATIONS

Model: TR800

AVERAGE POWER CONSUMPTION [Passive Antenna Connected]	CURRENT @ 15V AVERAGE	POWER
Standby	0.17 A	2.6 W
Transmit (RJ11/POTS call)	0.31 A	4.7 W
Transmit (Spreakerphone)	0.27 A	4.0 W
Peak Current	0.70 A	10.5 W
PHYSICAL SPECIFICATION	s	-
Dimensions	241 x 185 x 93 (mm)	9.49 x 7.28 x 3.66 (inches
Weight TR800 Only	1.27kg	2.8015
ENVIRONMENT SPECIFICA	TIONS	
Operation	-20°C to +55°C	-4°F to +131°F
Storage	-30°C to +80°C	-22°F to +176°F
Humidity		<=75% RH
TRANSCEIVER	25	
Inmarsat - 4 Satellite GMR - 2+ Frequency Bands	3	
Tx Operating Frequency	1626.5 - 1660.5 MHz	
Rx Operating Frequency	1518 - 1565 MHz (Inmarsat) 1565.19 - 585.65 MHz (GPS)	
RF Output Impedance	50 Ohms	
Carrier Frequencies	Channel 0 = 1626.525 MHz Channel 169 = 1660.475 MHz	
TX Modulation	GMSK	
RX Modulation	OQPSK	
CONNECTORS / INTERFAC	CES	
POTS/RJ11	RJ11/2-wire, 5REN @ 600m, Adjustable dial, ring, busy tone configured frequency and adaptive impedance.	
Inmarsat Antenna	TNC-Female	
	SMA-Female	
GPS Antenna	SMA-Female	

Privacy Hands	et Port	RJ9 connector	
Configuration,	/Data*	USB Mini B	
Speakerphone)ji	In-built speaker/microphone	
CERTIFICATIO	NS		
Inmarsat, FCC, C-Tick	CE Compliano	ce, Electrical Safety, RoHS, Industry Canada,	
	against water	mited ingress (no harmful deposits). r sprayed from all directions - limited	
KIT CONTENT	S		
Terra 800			
ISD700 Direct	ional/Fixed Ar	ntenna (Passive)	
Privacy Hands	et		
110 - 240V A	C Plug Pack 15	5v DC Out	
10 - 32V DC P	ower Cable		
1 x Spring cup	(attached to t	erminal)	
1 x Springless	cup		
USB Cable			
2m Alert wirin	g loop		
Wall mounting	plate		
User manual			
Quick Start Gu	ide		
ACCESSORIES	5		
LTO	LeoTRAK-	Online - www.leotrak.com	
ISD936	IsatDock 1	10m SMA/TNC cable kit [Passive]	
ISD937	IsatDock 2	20m SMA/TNC cable kit (Passive)	
ISD939	IsatDock 3	30m SMA/TNC cable kit (Passive)	
ISD940	IsatDock 4	40m SMA/TNC cable kit [Passive]	
ISD941	IsatDock 5	ck 50m SMA/TNC cable kit [Passive]	
RST055	Beam UPS Battery Pack		

APPROVED BEAM RESELLER



Phone: +1 (954) 973-3100 Web: www.gmpcs-us.com NetworkInnovations
Phone: +1 (403) 287-5000
Web: www.networkinv.com



TOLL FREE 1-888-989-8199

1455 N. Dutton Suite A, Santa Rosa, CA 95401 FAX 707-546-8198 • info@remotesatellite.com www.remotesatellite.com

AFRICA ASIA AUSTRALIA EUROPE MIDDLE EAST NORTH AMERICA SOUTH AMERICA