

Sea Tel USAT 30

Marine stabilized antenna system compatible with Ku-Band satellites

2013 Data Sheet

The most important thing we build is trust

COBHAM

USAT 30 Ku-Band Antenna

The USAT 30 is the latest in the long line of how-did-we-ever-live-without-this technology products from Sea Tel that are redefining global maritime communications. Our edge-of-your-seat products are not just breaking the mold, but busting through it.

The USAT 30 Ku-band antenna is a 75 cm Ultra Small Aperture Terminal marine stabilized antenna system for broadband connectivity. Incorporated in the design are some of the leading technology

concepts to reduce its size and match the performance of some of our bigger systems. It complements our range of other USAT and VSAT antennas; it is aesthetically pleasing for mega yachts as well as rugged enough for a workboat. The platform is designed to become part of the ship. It withstands the harshest weather nature can throw at it. In fact, that is practically what we do when we test our systems.

USAT 30 is not designed for compromise.

It is packed with high performance features that track satellites faster than the wind can change direction or the tides can swell. The pointing accuracy of this antenna is a result of over 10 million person hours of development effort. Perhaps that is the number one reason why Sea Tel antennas often work trouble free for years and years.

Go ahead, explore the edges of the world but always stay at the center of your communication needs with Sea Tel.

USAT 30 Key Benefits

- Better antenna performance of almost 3 dB allows sailing further out on the fringes of the footprint.*
- Higher carrier to noise ratio allows even more reliable communications anywhere within the footprint.
- Trend-blazing pointing accuracy of better than 0.2°
- Works with or without ship's gyro
- Lighter weight
- Install in hours instead of days
- Access remotely from anywhere and anytime




*When compared to similar antennas

Sea Tel USAT 30

Marine stabilized antenna system compatible with Ku-Band satellites

COBHAM



Typical data for USAT 30, Ku-Band

- Antenna: 75 cm/30", Ring Focus feed with motorized AutoPol
- Transmit Gain: 39.0 dBi @ 14.25 GHz
- Receive Gain: 37.0 dBi @ 11.85 GHz
- G/T: 16 dB/K calculated at 12 GHz (clear sky @ 30 degrees elevation)
- Meets FCC EIRP Spectral Density Mask @ 17.4 dBW/4 KHz output EIRPsd
-21.6 dBW/4 KHz input EIRPsd
- Pedestal Type: Closed Loop Servo
- Pointing Accuracy: 0.2° RMS @ 20° roll
- Elevation Range of Motion: +2° to +75°
- Azimuth Range of Motion: 680°
- Radome Dimensions: 0.94m/36.9in D x 1.016m/40in H (1m/39in max flange diameter)
- Total Weight with Radome: 132 lbs/60 kgs

Typical data for DAC 2202 Controller

- Model: 2202
- Mounting: Rack Mount
- M & C Ports: 1 Serial, 3 TCP/IP, 1 multi-user web browser support
- UDP Upload port for updating software in the Comm Interface
- Reformatted GPS output: (GGA and GLL)
- Heading Input: NMEA 0183, SBS, Synchro or No-Gyro Mode
- Dimensions: 19" X 1.75"

 **Remote Satellite Systems**
INTERNATIONAL

TOLL FREE 1-888-989-8199

1455 N. Dutton Suite A, Santa Rosa, CA 95401
FAX 707-546-8198 • info@remotesatellite.com
www.remotesatellite.com