

ASE-9575-HQ

 Remote Satellite Systems  
INTERNATIONAL

# ASE RESILIENCE

applied satellite  
engineering 

— ASE HEADQUARTERS DOCK —  
*(supports PTT)*



***EXTEND*** YOUR IRIDIUM REACH

# ASE RESILIENCE

## *EXTEND* YOUR IRIDIUM REACH

- ✓ HEADQUARTERS VOICE
- ✓ PTT ENABLED!
- ✓ SUPPORTS EXTERNAL SPEAKER FOR CONFERENCE CALLS
- ✓ INTEGRATION WITH OFFICE INFRASTRUCTURE VIA POTS SYSTEM



### **ALSO AVAILABLE: ASE-9575-BAGDOCK**

ASE-9575-BAGDOCK is a battery powered dock that supports both the standard 9575 Extreme and the 9575 PTT.

This dock provides communication on the move in a compact, portable package.

# ASE RESILIENCE



## WHAT'S IN THE BOX?

### ASE-9575-HQ-P

**CONTENTS:**  
 docking cradle  
 swivel/desk wall mount  
 fist mic/speaker  
 ac/dc adapter



### ASE-9575-HQ-H

**CONTENTS:**  
 docking cradle  
 swivel/desk wall mount  
 intelligent handset  
 ac/dc adapter

## OPTIONAL ACCESSORIES

**ASE-FA12**  
**ASE-FA20**  
 external antenna



**ASE-MNT03**  
 privacy handset  
 and mount bracket



**ASE-SPK01**  
 external speaker



**ASE-MNTE2**  
 fist mic/speaker  
 and mount bracket



## ASE-9575-HQ



TOLL FREE 1-888-989-8199

1455 N. Dutton Suite A, Santa Rosa, CA 95401  
 FAX 707-546-8198 • info@remotesatellite.com  
 www.remotesatellite.com

### ELECTRICAL SPECIFICATIONS

Operating Voltage	10 - 32 VDC
Power Consumption	12 Watts (Avg Active)

### ENVIRONMENTAL SPECIFICATIONS

Operating Temp Range	0°C to +70°C
Exposure	Indoor

### MECHANICAL DIMENSIONS

Dimensions	7L x 7W x 5H inches (18 x 18 x 13 cm)
Weight	2.5 lbs (1.13kG)
Mounting	Swivel desk/wall mount

### SHIPPING DIMENSIONS

Dimensions	14L x 10W x 6H inches (36 x 25 x 15 cm)
Weight	5 lbs (2.27 kG)