

# MODEL1258

MOBILE VSAT



## 1.2m Motorized Transportable Vehicle-Mount Antenna

### UNIQUE FEATURES

1.2m AvL Engineered Composite Reflector  
Zero Backlash AvL Cable Drive  
Compact/Rugged Pol Gear Drive  
Optional Rotary Joint on Pol Axis with Flex W/G to BUC  
"One-Button" Auto-Acquisition

### STANDARD Rx/Tx FEED

2-Port Ku-Band Precision (standard Cross-Pol comp.)

### POLARIZATION ADJUSTMENT

Motorized Worm Gear Drive

### LOW STOW

Stows up to 15"H (38.1 cm H)

# MODEL1258

MOBILE VSAT

## MECHANICAL

**AZ/EL DRIVE** --- Motorized AvL Zero Backlash Cable Drive (Patent Pending)

**POLARIZATION DRIVE SYSTEM** --- Motorized Worm Gear Drive

**REFLECTOR CONSTRUCTION** --- 1.2m Single Piece AvL Engineered Composite

### AXIS TRAVEL:

Azimuth --- 400° ( $\pm 200^\circ$ )

Elevation --- 0-90° antenna bore sight (true elevation readout from calibrated inclinometer)

Electrical --- Standard limits at 5° to 65° (CE Approval) or 0° to 90°

Polarization ---  $\pm 95^\circ$

### AZ/EL SPEED:

Slewing/Deploying (typical) --- 2°/second

Peaking (typical) --- 0.2°/second

**MOTORS** --- 24 VDC Variable Speed, Constant Torque

### RF INTERFACE:

BUC/HPA Mounting --- Feed Boom (maximum weight 25 lbs.(11.3 kg))

Max dimensions for BUC mounting on Feed Boom --- 22 L x 13.8 W x 8.5 H in. (56 L x 35 W x 22 H cm)

Feed Tx --- Polarization RJ w/flex waveguide from feed, WR75

**COAX** --- Two Type F connectors at antenna base

**ELECTRICAL INTERFACE** --- One 25 ft. (8 m) cable with connector to controller

**MANUAL/EMERGENCY DRIVE** --- Hand crank input on Az, El and Pol axes

**WEIGHT (APPROX)** --- 100 to 120 lbs. (46 to 55 kg) depending on options

**STOWED DIMENSIONS** --- 70 L x 48 W x 15 H inches (178 L x 122 W x 38 H cm) including pallet

**TIME TO ACQUISITION** --- Less than 10 minutes, 8 minutes typical

**MOUNTING** --- Pallet for vehicle roof mounting

## ENVIRONMENTAL

**WIND - SURVIVAL** --- Deployed: 65 mph (105 kph); Stowed: 80 mph (129 kph)

**WIND- OPERATIONAL** --- 45 mph (72 kph)

**POINTING LOSS IN WIND (Ku RX):**

20 mph (32 kph) --- 0.5 dB typical

30 mph gusting to 45 mph (48 kph gusting to 56 kph) --- 1.2 dB typical

**TEMPERATURE:**

Operational --- -22° to 125° F (-30° to 52° C)

Survival --- -40° to 140° F (-40° to 60° C)



**TOLL FREE 1-888-989-8199**

1455 N. Dutton Suite A, Santa Rosa, CA 95401  
FAX 707-546-8198 • [info@remotesatellite.com](mailto:info@remotesatellite.com)  
[www.remotesatellite.com](http://www.remotesatellite.com)